



Type	Top Surface		Drive Surface		Max. width [mm]	Overall thickness aR [mm]	Tensile strength [N/mm]	Tractive force 1 % elongation FZ1% [N/mm]	Min. Pulley diameter dmin [mm]	Working temperatures				Final bonding		
	colour	colour	min.	max.						min.	max.	Adhesive type	Pressing time min.	Pressing temp. °C		
GG-ELAST	Rubber textured		Rubber textured	Black	1000	1,5		2,0	15	-20	100	-30	130	FXS	30	90-120
5-N3	Rubber textured	Blue	Rubber textured	Blue	500	3,0	225	6,0	30	-20	100	-30	130	FX+FXS	30	90-120
5-N4	Rubber textured	Blue	Rubber textured	Blue	500	4,0	225	6,0	30	-20	100	-30	130	FX+FXS	30	90-120
5-N5	Rubber textured	Blue	Rubber textured	Blue	500	5,0	225	6,0	50	-20	100	-30	130	FX+FXS	30	90-120
5-N6	Rubber textured	Blue	Rubber textured	Blue	500	6,0	225	6,0	50	-20	100	-30	130	FX+FXS	30	90-120
5-N3-SG	Rubber textured	S.Green	Rubber textured	S.Green	500	3,0	225	6,0	30	-20	100	-30	130	FX+FXS	30	90-120
5-N4-SG	Rubber textured	S.Green	Rubber textured	S.Green	500	4,0	225	6,0	30	-20	100	-30	130	FX+FXS	30	90-120
5-N5-SG	Rubber textured	S.Green	Rubber textured	S.Green	500	5,0	225	6,0	50	-20	100	-30	130	FX+FXS	30	90-120
5-N6-SG	Rubber textured	S.Green	Rubber textured	S.Green	500	6,0	225	6,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-N6	Rubber textured	Blue	Rubber textured	Blue	500	6,0	450	11,0	75	-20	100	-30	130	FX+FXS	40	90-120
10-NG6	Rubber textured	Grey	Rubber textured	Grey	500	6,0	450	11,0	75	-20	100	-30	130	FX+FXS	40	90-120
5-LNT	Rubber textured	Red	Carbon Fabric	Black	500	4,0	225	5,0	30	-20	100	-30	130	FX+FXS	30	90-120
5-LNG	Rubber textured	Red	Rubber textured	Blue	500	6,8	225	7,0	50	-20	100	-30	130	FX+FXS	30	90-120
3-TS 2	Rubber textured	M.Green	Carbon Fabric	Black	500	2,0	135	4,0	25	-20	100	-30	130	FX+FXS	30	90-120
5-TS 2	Rubber textured	M.Green	Carbon Fabric	Black	500	2,2	225	5,0	30	-20	100	-30	130	FX+FXS	30	90-120
7-TS 2	Rubber textured	M.Green	Carbon Fabric	Black	500	2,4	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
5-TS 3	Rubber textured	S.Green	Carbon Fabric	Black	500	3,0	225	5,0	30	-20	100	-30	130	FX+FXS	30	90-120
7-TS 3	Rubber textured	S.Green	Carbon Fabric	Black	500	3,2	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-TS 3	Rubber textured	S.Green	Carbon Fabric	Black	500	3,5	450	11,0	70	-20	100	-30	130	FX+FXS	40	90-120
5-TS 6	Rubber textured	M.Green	Carbon Fabric	Black	500	5,8	225	6,0	50	-20	100	-30	130	FX+FXS	30	90-120
7-TS 6	Rubber textured	M.Green	Carbon Fabric	Black	500	6,0	315	8,0	70	-20	100	-30	130	FX+FXS	30	90-120
10-TS 6	Rubber textured	M.Green	Carbon Fabric	Black	500	6,2	450	11,0	100	-20	100	-30	130	FX+FXS	40	90-120
5-MGR 2	Rubber textured	T.Green	Carbon Fabric	Black	500	2,5	225	6,0	30	-20	100	-30	130	FX+FXS	30	90-120
7-MGR 2	Rubber textured	T.Green	Carbon Fabric	Black	500	2,7	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-MGR 2	Rubber textured	T.Green	Carbon Fabric	Black	500	3,0	450	12,0	70	-20	100	-30	130	FX+FXS	40	90-120
5-GR 6	Rubber textured	M.Green	Carbon Fabric	Black	500	6,0	225	6,0	100	-20	100	-30	130	FX+FXS	30	90-120
7-GR 6	Rubber textured	M.Green	Carbon Fabric	Black	500	6,0	315	8,0	100	-20	100	-30	130	FX+FXS	30	90-120