

Type	Top Surface		Drive Surface		Max. width [mm]	Overall thickness aR [mm]	Tensile strength [N/mm]	Tractive force 1 % elongation FZ1% [N/mm]	Min. Pulley diameter amin [mm]	Working temperatures				Final bonding		
	colour	colour	°C	°C						°C	°C	Adhesive type	Pressing time min.	Pressing temp. °C		
5-XR1/GM	Rubber textured	D.Blue	Rubber textured	Grey	500	2,5	225	5,0	25	-20	100	-30	130	FX+FXS	30	90-120
7-XR1/GM	Rubber textured	D.Blue	Rubber textured	Grey	500	2,7	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-XR1/GM	Rubber textured	D.Blue	Rubber textured	Grey	500	3,0	450	10,5	70	-20	100	-30	130	FX+FXS	40	90-120
15-XR1/GM	Rubber textured	D.Blue	Rubber textured	Grey	500	3,5	675	15,0	125	-20	100	-30	130	FX+FXS	45	90-120
20-XR1/GM	Rubber textured	D.Blue	Rubber textured	Grey	500	4,1	900	22,0	280	-20	100	-30	130	FX+FXS	50	90-120
5-XR/GM	Rubber textured	Blue	Rubber textured	Grey	500	2,0	225	5,0	25	-20	100	-30	130	FX+FXS	30	90-120
7-XR/GM	Rubber textured	Blue	Rubber textured	Grey	500	2,2	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-XR/GM	Rubber textured	Blue	Rubber textured	Grey	500	2,6	450	10,5	70	-20	100	-30	130	FX+FXS	40	90-120
15-XR/GM	Rubber textured	Blue	Rubber textured	Grey	500	3,0	675	15,0	125	-20	100	-30	130	FX+FXS	45	90-120
3-XS	Rubber textured	T.Green	Rubber textured	Black	500	1,8	135	4,0	20	-20	100	-30	130	FX+FXS	20	90-120
5-XS	Rubber textured	T.Green	Rubber textured	Black	500	2,0	225	5,0	25	-20	100	-30	130	FX+FXS	30	90-120
7-XS	Rubber textured	T.Green	Rubber textured	Black	500	2,2	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-XS	Rubber textured	T.Green	Rubber textured	Black	500	2,6	450	10,5	70	-20	100	-30	130	FX+FXS	40	90-120
15-XS	Rubber textured	T.Green	Rubber textured	Black	500	3,0	675	15,0	125	-20	100	-30	130	FX+FXS	45	90-120
5-XR/SS	Rubber textured	Yellow	Rubber textured	Black	500	2,0	225	5,0	25	-20	100	-30	130	FX+FXS	30	90-120
7-XR/SS	Rubber textured	Yellow	Rubber textured	Black	500	2,2	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-XR/SS	Rubber textured	Yellow	Rubber textured	Black	500	2,6	450	10,5	70	-20	100	-30	130	FX+FXS	40	90-120
15-XR/SS	Rubber textured	Yellow	Rubber textured	Black	500	3,0	675	15,0	125	-20	100	-30	130	FX+FXS	45	90-120
5-XR/SG	Rubber textured	Grey	Rubber textured	Black	500	2,0	225	5,0	25	-20	100	-30	130	FX+FXS	30	90-120
7-XR/SG	Rubber textured	Grey	Rubber textured	Black	500	2,2	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-XR/SG	Rubber textured	Grey	Rubber textured	Black	500	2,6	450	10,5	70	-20	100	-30	130	FX+FXS	40	90-120
15-XR/SG	Rubber textured	Grey	Rubber textured	Black	500	3,0	675	15,0	125	-20	100	-30	130	FX+FXS	45	90-120
5-XR/SM	Rubber textured	Blue	Rubber textured	Black	500	2,0	225	5,0	25	-20	100	-30	130	FX+FXS	30	90-120
7-XR/SM	Rubber textured	Blue	Rubber textured	Black	500	2,2	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-XR/SM	Rubber textured	Blue	Rubber textured	Black	500	2,6	450	10,5	70	-20	100	-30	130	FX+FXS	40	90-120
15-XR/SM	Rubber textured	Blue	Rubber textured	Black	500	3,0	675	15,0	125	-20	100	-30	130	FX+FXS	45	90-120
5-XR/YM	Rubber textured	T.Green	Rubber Smooth	Blue	500	2,0	225	5,0	25	-20	100	-30	130	FX+FXS	30	90-120
7-XR/YM	Rubber textured	T.Green	Rubber Smooth	Blue	500	2,2	315	8,0	50	-20	100	-30	130	FX+FXS	30	90-120
10-XR/YM	Rubber textured	T.Green	Rubber Smooth	Blue	500	2,6	450	10,5	70	-20	100	-30	130	FX+FXS	40	90-120
15-XR/YM	Rubber textured	T.Green	Rubber Smooth	Blue	500	3,0	675	15,0	125	-20	100	-30	130	FX+FXS	45	90-120